

TECHNICAL DATA SHEET



Last updated: 19.11.2009

Product Codes: RCCASF10

RUNCUT CASF 10 is an extreme pressure neat cutting oil blended from solvent refined mineral oil using selected additives, affording a high level of lubricity and EP performance.

APPLICATION

Suitable for machining a wide range of materials in various applications, including deep hole boring, broaching, H.D. tapping, threading and gear cutting. Arduous operations are overcome using high performance EP package.

BENEFITS

- Enhanced lubricity with high EP.
- Good workplace visibility.
- Improved finish on machine parts
- Low oil mist levels.
- Promotes extended tool life.

TYPICAL PROPERTIES

Appearance:	Dark Amber Fluid
Specific Gravity @ 15.6°C:	0.876
Kinematic Viscosity @ 40°C:	9.2 – 11.00 cSt
Sulphur:	Active
Chlorine:	Yes
Ester:	Yes

HEALTH & SAFETY

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Material Safety Data Sheet is available.

Indicated data are approximate values and are subject to the usual commercial fluctuations. All information correct at time of going to press to the best of our knowledge. This information may be subject to change without notification due to continual product research and development.

MTO Lubricants (Part of Milo Tools Ltd)

Tel: 01274 872822

Fax: 0113 8800541

Email: sales@milotools.co.uk

Registered In England 08809951 VAT Registration No. GB 184 4633 89

