

# TECHNICAL DATA SHEET



Last updated: 19.11.2009

Product Codes: RSWHEP

**RUNSOL WHITEWATER EP** is a high performance, emulsion soluble cutting fluid suitable for a wide range of applications.

## BENEFITS

- High oil content.
- Exceptional cooling properties.
- Good anti-corrosion inhibition to ferrous metals.
- EP additives ensure good tool cutting and high quality surface finish.
- Boron, formaldehyde, nitride and phenol free formulation for optimum operator acceptability.

## APPLICATIONS

Recommended treat rate 3-8% in water, depending on severity of application. Minimum treat rate 3% in water

	Turning	Drilling / Milling	Sawing	Grinding	Honing	Lapping	Threading	Deep Hole Drilling	Broaching
Steel	✓	✓	✓				✓		
Stainless steel	✓	✓	✓				✓		
High Alloy Steel	✓	✓	✓				✓		
Titanium									
Carbide									
Cast Iron	✓	✓	✓				✓		
Copper Alloys	✓	✓	✓				✓		
Aluminium Alloys < 7% Si	✓	✓	✓				✓		
Aluminium Alloys > 7% Si									
Plastic	✓	✓	✓				✓		

Water hardness should be checked to determine optimum running concentrations, please consult your MTO Lubricants sales engineer for further details.

## TYPICAL PROPERTIES

Appearance:	Forms a white milky emulsion
Specific Gravity @ 15.6°C:	0.90
pH (3% solution)	8.9

1/2

MTO Lubricants (Part of Milo Tools Ltd)

Tel: 01274 872822

Fax: 0113 8800541

Email: [sales@milotools.co.uk](mailto:sales@milotools.co.uk)

Registered In England 08809951 VAT Registration No. GB 184 4633 89



# TECHNICAL DATA SHEET



## FLUID MAINTENANCE

Refractive Index: - 1.0 = % / °Brix

Refractometry data for Runsol Whitewater EP	
Refractometer reading	Actual Concentration
0	0
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11

## HEALTH & SAFETY, STORAGE AND DISPOSAL

**RUNSOL WHITEWATER EP** should be stored in dry conditions and protected from extreme temperatures: between 4°C and 35°C is the recommended storage temperatures.

**RUNSOL WHITEWATER EP** is unlikely to present any significant health or safety hazard when used as recommended by MTO Lubricants. Good standards of personal and industrial hygiene are to be maintained by the user (see Material Safety Data Sheets). In order to protect the environment, the product used should be safely disposed of by a licensed contractor. The packaging material should be handled by a recognized reconditioning firm.

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT.

MTO Lubricants assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless injury or damage is solely attributable to negligence on the part of MTO Lubricants

2/2

MTO Lubricants (Part of Milo Tools Ltd)

Tel: 01274 872822

Fax: 0113 8800541

Email: [sales@milotools.co.uk](mailto:sales@milotools.co.uk)

Registered In England 08809951 VAT Registration No. GB 184 4633 89

